

I/O Karte für Drucker 2
I/O Board for printer 2

(SAAG21) AAG21
701.81707

Position-Nr. Position-No.	Typ Type	Teil-Nr. Part-No.	Bemerkung Remarks
<u>IC - Bausteine / IC - chips</u>			
IC 50,60	SN 7400 N	E 600.37001	A 01
IC 43,46	SN 7402 N	E 600.37003	A 02
IC 13I,13II, 20I,20II, 27I,27II, 34I,34II, 35I,35II, 41I,41II, 68I,68II	SN 75453 BP	E 600.37058	A 28
IC 12,18,19, 25,26,33, 39,40,45, 47,53,54, 57,61	SN 7475 N	E 600.37040	F 04
IC 67	SN 7474 N	E 600.37042	F 06
IC 74,81	SN 74221 N	E 600.37048	G 06
IC 2,9,16, 23,37,44, 51,30	SN 74151 N	E 600.37015	H 02
IC 8	SN 7430 N	E 600.37008	A 06
IC 49,56	SN 7438 N	E 600.37028	A 14
IC 22,66,71	SN 7405 N	E 600.37024	A 11
IC 1,15,63	SN 7404 N	E 600.37006	A 03
IC 59,64	SN 74155 N	E 600.37050	H 05
IC 29,36,58, 65	SN 7437 N	E 600.37027	A 18
IC 77	SN 74132 N	E 600.37052	G 04
IC 70	SN 7493 N	E 600.37021	P 01

Position-Nr. Position-No.	Typ Type	Teil-Nr. Part-No.	Bemerkung Remarks
<u>Transistoren / Transistors</u>			
T 1-4	BD 679	E 600.63047	
<u>Dioden / Diodes</u>			
D 1-4	1 N 4001	E 600.64042	
D 7,8	1 N 4448	E 600.64027	
<u>Kondensatoren / Capacitors</u>			
C 5-24, 28,32-35	0,1 μ F 100 V	E 600.52032	
C 2-4,25, 26,27,36, 37,38	0,1 μ F 16 V	E 600.53010	
C 29,31,39	1000 pF 100 V	E 600.52025	
C 1	100 μ F 16 V	E 600.50061) wahlweise) alternatively
	100 μ F 16 V	E 600.50070	
C 30	4700 pF 100 V	E 600.52028	
C 40	220 μ F 40 V	E 600.50010	
<u>Widerstände / Resistors</u>			
R 36,38,40, 42,46,48, 50,51	1 kOhm 1/8 W	E 600.40195	
R 47	1,2 kOhm 1/8 W	E 600.40210	
R 58	2,7 kOhm 1/8 W	E 600.40196	
R 56	4,7 kOhm 1/8 W	E 600.40197	
R 1-20,54	10 kOhm 1/8 W	E 600.40200	

Position-Nr. Position-No.	Typ Type	Teil-Nr. Part-No.	Bemerkung Remarks
<u>Widerstände / Resistors</u>			
R 44,45	22 kOhm	1/8 W E 600.40208	
R 37,39,41, 43	47 Ohm	1/4 W E 600.40104	
R 23,25-33	100 Ohm	1/4 W E 600.40108	
R 59	470 Ohm	1/8 W E 600.40193	
R 55,57	10 kOhm	1/2 W E 600.44033	
R 21,22,24, 34,35,49, 52,53, 60-68	47 Ohm	1/8 W E 600.40205	
<u>Allgemeine Teile / General parts</u>			
Sch. 1,2	0,1 A 100 V	E 600.85059 E 600.85073	Schalter) wahlweise Switch) alternatively
M 38,72,76, 78,79,84	8 pol.	E 600.23115	Stiftleiste) Pin bar) wahlweise
	8 pol.	E 435.02532	Kontaktstift) alternat. Contact pin)
	2 pol.	E 600.23121	Federleiste) wahlweise
	8 pol.	E 600.23127	Spring contact strip) al- ternatively
Abb. 1 Pict.1	24 pol.	E 600.23123	Sockel Socket
Abb. 2 Pict.2	40 pol.	E 600.23057	Buchsenleiste Bushing strip
Abb. 3 Pict.3		301.00481	Meßpunktstift Measuring point pin
Abb. 4 Pict.4		403.30055	Rohrniet Tubular rivet

